

AIS Party Wall Firestop Batt

Product Description

AIS Party Wall Firestop Batts are rigid non-combustible stonewool batts insulation designed to protect the opening in fire-resistant separating elements.

AIS Party Wall Firestop Batts are available in a range of sizes and a 100mm thick specimen was tested in accordance to AS 1530.4 providing a fire resistance level (FRL) of - /240/120.



Application

AIS Party Wall Firestop Batts are commonly used for fire protection between partition walls and the roofing material. Single layer applications are preferred and for control joints, a minimum of 10% compression shall be ensured to allow for joint expansion movements.

Please consult with the relevant authority on the suitability of the application.

Product Dimensions

Product Code	Thickness (mm)	Nominal Length (mm)	Nominal Width (mm)	Pack Qty
115011405.150	100	1200	150	12
115011405.168	100	1200	168	5

Product Properties

Properties	Standard	Performance
Melting point	ASTM E794	>1000°C
Fire performance	AS 1530.1	Non-combustible
Nominal density	EN 13470	80 Kg/m ³
Water Absorption (partial immersion)	EN 1609.97	0.5 Kg/m ²
*R-Value 100mm thk (m ² K/W)	AS 4859.1	2.80

Australasian Insulation Solutions Pty Ltd (AIS). AIS reserves the right to change product specification without prior notice. Technical specifications as shown in this document are intended to be used as general guidelines only. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. AIS takes no responsibility for errors herein contained in this document.

For the most current version of this publication, please refer to ais-group.com.au.

Distributed by Australasian Insulation Solutions Pty Ltd (AIS) ///
 Contact AIS for more information ///
sales@ais-group.com.au ///
 Ph: +61 08 9417 9494 ///
www.ais-group.com.au ///

Version No: TDS_0124-1-V1
 Supersedes: N/A

