

# AIS Party Wall Firestop Roll

## Product Description

AIS Party Wall Firestop Rolls are flexible non-combustible stonewool roll insulation designed to protect the opening in fire-resistant separating elements. They are available with or without foil facing.

## Application

AIS Party Wall Firestop Rolls are commonly used for inter-tenancy walls in multi residential applications. Please consult with the relevant authority on the suitability of the application.

## Technical Specification

When specifying, state the following:

The insulation material shall be AIS Party Wall Firestop Roll \_\_\_\_ (thickness) x \_\_\_\_ (width) \_\_\_\_ (length) mm.

## Product Dimensions

Product Code	Facing	Thickness (mm)	Nominal Length (mm)	Nominal Width (mm)	Pack Qty
115001505.50-200	N/A	50	5000	200	3
115001505.50-300	N/A	50	5000	300	2
115001505.50-200F	Foil Facing (one side)	50	5000	200	3
115001505.50-300F	Foil Facing (one side)	50	5000	300	2

## Product Properties

Properties	Standard	Performance
Melting point	ASTM E794	>1000°C*
Fire performance	AS 1530.1	Non-combustible*
Nominal density	EN 13470	80 Kg/m <sup>3</sup>
Water Absorption (partial immersion)	EN 1609.97	0.5 Kg/m <sup>2</sup>
*R-Value 50mm thk (m <sup>2</sup> K/W)	AS 4859.1	1.45

\*Applies to Stonewool insulation



Example shown has foil facing.

Australasian Insulation Solutions Pty Ltd (AIS). AIS reserves the right to change product specification without prior notice. Technical specifications as shown in this document are intended to be used as general guidelines only. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. AIS takes no responsibility for errors herein contained in this document.

For the most current version of this publication, please refer to [ais-group.com.au](http://ais-group.com.au).

Distributed by Australasian Insulation Solutions Pty Ltd (AIS) ///  
 Contact AIS for more information ///  
[sales@ais-group.com.au](mailto:sales@ais-group.com.au) ///  
 Ph: +61 08 9417 9494 ///  
[www.ais-group.com.au](http://www.ais-group.com.au) ///

Version No: TDS\_1725-1-V1  
 Supersedes: N/A

