

Party Wall Firestop Roll

Product Description

Party Wall Firestop Rolls are flexible non-combustible ROCKWOOL® roll insulation designed to protect the opening in fire-resistant separating elements.

Party Wall Firestop Rolls are available in a range of sizes and a 100mm tick specimen was tested in accordance to AS 1530.4 providing a fire resistance level (FRL) of -/240/120.



Application

Party Wall Firestop Rolls are commonly used for inter-tenancy walls in multi residential applications.

Please consult with the relevant authority on the suitability of the application.

Product Dimensions

Product Code	Thickness (mm)	Nominal Length (mm)	Nominal Width (mm)	Pack Qty
101050201.50	50	5000	200	3
101050201.50-300	50	5000	300	2
101050201.75	75	4000	300	2

Product Properties

Properties	Standard	Performance		
Melting point	ASTM E794	>1000°C*		
Fire performance	AS 1530.1	Non-combustible*		
Nominal density	EN 13470	80 Kg/m³		
Water Absorption (partial immersion)	EN 1609.97	0.5 Kg/m²		
*R-Value 50mm thk (m²K/W)	AS 4859.1	1.45		
*Applies to Rockwool insulation				

Australasian Insulation Solutions Pty Ltd (AIS). AIS reserves the right to change product specification without prior notice. Technical specifications as shown in this document are intended to be used as general guidelines only. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. AIS takes no responsibility for errors herein contained in this document.

For the most current version of this publication, please refer to ais-group.com.au.

