

# Rockpipe

## Product Description

Rockpipe is a Rockwool pipe section. The insulation sections are made from high-quality stone wool to mitigate the risk of corrosion under insulation.

A reinforced aluminium foil facing is available upon request.

Rockpipe insulation sections are supplied in 1m lengths.



## Application

The highly durable insulation sections are supplied split and hinged for easy snap on assembly and are especially suitable thermal and acoustic insulation for industrial, HVAC and plumbing pipe work.

The material complies with AS/NZS 4859.1 and fire requirements of AS 1530.1 and 1530.4.

## Product Properties

Properties	Performance	Note
Maximum service temperature	650°C	ASTM C411
Melting point	>1000°C	ASTM E794
Fire performance	Non-combustible	EN 1350-1, AS 1530.1 - 1530.4
Thermal conductivity	0.034 W/mK	ASTM C518
Nominal density available	90 - 110 Kg/m <sup>3</sup>	EN 13470
Corrosion resistance	Trace quantity of water leachable chloride ions: ≤ 10 ppm	EN 13468
Water absorption (partial immersion)	Less than 1.0 Kg/m <sup>2</sup>	BS EN ISO 29767
Moisture absorption	< 0.04% volume	ASTM C1104

Australasian Insulation Solutions Pty Ltd (AIS). AIS reserves the right to change product specification without prior notice. Technical specifications as shown in this document are intended to be used as general guidelines only. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. AIS takes no responsibility for errors herein contained in this document.

For the most current version of this publication, please refer to [ais-group.com.au](http://ais-group.com.au).

Distributed by Australasian Insulation Solutions Pty Ltd (AIS) ///  
 Contact AIS for more information ///  
[sales@ais-group.com.au](mailto:sales@ais-group.com.au) ///  
 Ph: +61 08 9417 9494 ///  
[www.ais-group.com.au](http://www.ais-group.com.au) ///

Version No: TDS\_2623-1-V2  
 Supersedes: TDS\_2623-1-V1

